

SPOTLIGHT LIDER B MINI 830 23W 38° BLACK | ON/OFF

Article number: N007-K0002-RF830-H5-M38-ZE52_600-S1-###





LED	COB	Spotlig
Light colour	3000 [K]	Compac installat colour a 60°. Ma
CRI	80	
Led chip flux	3266 [lm]	
Luminous flux System power	2939 [lm] 23 [W]	
Beam angle	38°	
Controller MacAdam	ON/OFF 3 SDCM	
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

ght LED

act track mounted LED spotlight. Aluminium housing. Ceiling base ation possible. Available in white, black and grey. Any RAL palette available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and aximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

SPOTLIGHT



