

SPOTLIGHT

SPOTLIGHT LIDER B MINI 835 25W 60° BLACK | ON/OFF

Article number: N007-K0002-RF835-H5-M60-ZE52_650-S1-###





| LED | COB | Spotlight LE |
|----------------------|------------|---|
| Light colour | 3500 [K] | Compact trad installation po colour availal 60°. Maximur |
| CRI | 80 | |
| Led chip flux | 3618 [lm] | |
| Luminous flux | 3256 [lm] | |
| System power | 25 [W] | |
| Luminaire Efficiency | 130 [lm/W] | |
| Beam angle | 60° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | _ |
| Weight | 0,85 [kg] | |
| | | |

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

.ED

ack mounted LED spotlight. Aluminium housing. Ceiling base possible. Available in white, black and grey. Any RAL palette able on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and um power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska