

SPOTLIGHT

SPOTLIGHT LIDER B MINI 927 14W 38° BLACK | ON/OFF

Article number: N007-K0002-RF927-H5-M38-ZE52_350-S1-###





LED	COB	Spotlight LED
Light colour	2700 [K]	Compact track m
CRI	80	installation possil colour available o
Led chip flux	1555 [lm]	60°. Maximum po
Luminous flux	1399 [lm]	
System power	14 [W]	
Luminaire Efficiency	100 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

nounted LED spotlight. Aluminium housing. Ceiling base sible. Available in white, black and grey. Any RAL palette on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska