

SPOTLIGHT

SPOTLIGHT LIDER B MINI 927 19W 60° BLACK | ON/OFF

Article number: N007-K0002-RF927-H5-M60-ZE52_500-S1-###





	LED	COB	Spotlight LE
	Light colour	2700 [K]	Compact trac installation po colour availat 60°. Maximur
	CRI	80	
	Led chip flux	2222 [lm]	
	Luminous flux	1999 [lm]	
	System power	19 [W]	
	Luminaire Efficiency	105 [lm/W]	
	Beam angle	60°	
	Controller	ON/OFF	
	MacAdam	3 SDCM	
L	UMINAIRE		
	Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

ED

ack mounted LED spotlight. Aluminium housing. Ceiling base possible. Available in white, black and grey. Any RAL palette able on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and um power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska