

SPOTLIGHT

SPOTLIGHT LIDER B MINI 927 27W 60° BLACK | ON/OFF

Article number: N007-K0002-RF927-H5-M60-ZE52_700-S1-###





L	ED	COB	Spotlight LED
L	ight colour	2700 [K]	Compact track me installation possib colour available o 60°. Maximum po
C	RI	80	
L	ed chip flux	3111 [lm]	
L	uminous flux	2799 [lm]	
S	System power	27 [W]	
L	uminaire Efficiency	104 [lm/W]	
E	Beam angle	60°	
C	Controller	ON/OFF	
N	/lacAdam	3 SDCM	
LUN	MINAIRE		
V	Veight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

nounted LED spotlight. Aluminium housing. Ceiling base ble. Available in white, black and grey. Any RAL palette on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and ower is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska