

SPOTLIGHT LIDER B MINI 930 21W 23° BLACK | ON/OFF

Article number: N007-K0002-RF930-H5-M23-ZE52_550-S1-###





LED	COB	Spotlig
Light colour	3000 [K]	Compa installa colour a 60°. Ma
CRI	90	
Led chip flux	2536 [lm]	
Luminous flux	2282 [lm]	
System power	21 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	23°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base nstallation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 50°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska SPOTLIGHT