

SPOTLIGHT LIDER B MINI 930 10W 23° BLACK | ON/OFF

Article number: N007-K0002-RF930-H5-M23-ZE62_250-S1-###





LED	СОВ	Spotlight LED
Light colour	3000 [K]	Compact track installation pos colour available 60°. Maximum
CRI	90	
Led chip flux	1152 [lm]	
Luminous flux	1036 [lm]	
System power	10 [W]	
Luminaire Efficiency	104 [lm/W]	
Beam angle	23°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

D

k mounted LED spotlight. Aluminium housing. Ceiling base ssible. Available in white, black and grey. Any RAL palette ble on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and m power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

SPOTLIGHT

