

## SPOTLIGHT LIDER B MINI 930 21W 38° BLACK | ON/OFF

Article number: N007-K0002-RF930-H5-M38-ZE52\_550-S1-###



LED	COB
Light colour	3000 [K]
CRI	90
Led chip flux	2536 [lm]
Luminous flux	2282 [lm]
System power	21 [W]
Luminaire Efficiency	109 [lm/W]
Beam angle	38°
Controller	ON/OFF
MacAdam	3 SDCM

### Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

### LUMINAIRE

Weight	0,85 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 01.09.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska