

SPOTLIGHT

SPOTLIGHT LIDER B MINI 940 10W 15° BLACK | ON/OFF

Article number: N007-K0002-RF940-H5-M15-ZE62_250-S1-###





LED	COB	Spotlight LE
Light colour	4000 [K]	Compact trac installation pc colour availat 60°. Maximur
CRI	90	
Led chip flux	1208 [lm]	
Luminous flux	1087 [lm]	
System power	10 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

ED

ack mounted LED spotlight. Aluminium housing. Ceiling base able on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and um power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska