

SPOTLIGHT LIDER B MINI 825 25W 15° BLACK BREAD ON/OFF

Article number: N007-K0002-VF825-H5-M15-ZE52_650-S1-###





Light colour COB
Light colour 2500 [K] BREAD

CRI 8

 CRI
 80

 Led chip flux
 3042 [lm]

 Luminous flux
 2737 [lm]

 System power
 25 [W]

 Luminaire Efficiency
 109 [lm/W]

 Beam angle
 15°

 Controller
 ON/OFF

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

 Weight
 0,85 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 BLACK

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 01.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska