

SPOTLIGHT LIDER B MINI 825 23W 60° BLACK BREAD ON/OFF

Article number: N007-K0002-VF825-H5-M60-ZE52_600-S1-###





LED COB

Light colour 2500 [K] BREAD

CRI 8

 Led chip flux
 2808 [lm]

 Luminous flux
 2527 [lm]

 System power
 23 [W]

Luminaire Efficiency 110 [lm/W]

Beam angle60°ControllerON/OFFMacAdam3 SDCM

LUMINAIRE

Weight 0,85 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 01.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska