

SPOTLIGHT LIDER B MINI 930 23W 15° WHITE HI EFFICIENT ON/OFF

Article number: N007-K0003-BB930-H5-M15-ZE53_600-S1-###



LED	СОВ
Light colour	3000 [K] HI EFFICIENT
CRI	90
Led chip flux	
Luminous flux	3787 [lm]
System power	3408 [lm]
	23 [W]
Luminaire Efficiency	148 [lm/W]
Beam angle	15°
Controller	15
MacAdam	ON/OFF
Nuo kum	3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

LUMINAIRE

Weight	0,85 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 01.09.2024