

SPOTLIGHT LIDER B MINI 940 14W 15° WHITE HI EFFICIENT ON/OFF

Article number: N007-K0003-BB940-H5-M15-ZE53_350-S1-###



3 SDCM



COB 4000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 2260 [lm] Luminous flux 2034 [lm] System power 14 [W] Luminaire Efficiency 145 [lm/W] Beam angle 15° Controller ON/OFF

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

LUMINAIRE

MacAdam

Weight 0,85 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska