

SPOTLIGHT LIDER B MINI 930 23W 15° WHITE CRI97 ON/OFF

Article number: N007-K0003-HI930-H5-M15-ZE53_600-S1-###



COB



Light colour	3000 [K] CRI97
CRI	90
Led chip flux	2601 [lm]
Luminous flux	2340 [lm]
System power	23 [W]
Luminaire Efficiency	102 [lm/W]
Beam angle	15°

Beam angle15°ControllerON/OFFMacAdam3 SDCM

LUMINAIRE

Weight	0,85 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 01.09.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska