

SPOTLIGHT

SPOTLIGHT LIDER B MINI 930 25W 45° WHITE CRI97 ON/OFF

Article number: N007-K0003-HI930-H5-M45-ZE53_650-S1-###



LED	COB	Spotlight LED
Light colour	3000 [K] CRI97	Compact track mounted LED sp installation possible. Available in colour available on enquiry. Ref 60°. Maximum power is 27W.
CRI	90	
Led chip flux	2797 [lm]	
Luminous flux	2517 [lm]	
System power	25 [W]	
Luminaire Efficiency	101 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
UMINAIRE		
Weight	0,85 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic

spotlight. Aluminium housing. Ceiling base in white, black and grey. Any RAL palette eflector beams available: 15°, 23°, 38°, 45° and

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska