

## SPOTLIGHT LIDER B MINI 930 19W 60° WHITE CRI97 ON/OFF

Article number: N007-K0003-HI930-H5-M60-ZE53\_500-S1-###



3 SDCM



COB 3000 [K] CRI97 Light colour

CRI

2199 [lm] Led chip flux Luminous flux 1979 [lm] System power 19 [W] Luminaire Efficiency 104 [lm/W] Beam angle 60° Controller ON/OFF

MacAdam

## LUMINAIRE

0,85 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska