SPOTLIGHT LIDER B MINI 830 25W 23° WHITE | ON/OFF

Article number: N007-K0003-RF830-H5-M23-ZE53_650-S1-###



LED	COB
Light colour	3000 [K] |
CRI	80
Led chip flux	3538 [lm]
Luminous flux	3184 [lm]
System power	25 [W]
Luminaire Efficiency	127 [lm/W]
Beam angle	23°
Controller	ON/OFF
MacAdam	3 SDCM

LUMINAIRE

Weight	0,85 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

Generated: 27.07.2024

+48 32 388 80 00

www.cora.pl
cora@cora.pl

Street: Ignatza Hakuby 18
41-914 Bytom, Polska