

SPOTLIGHT

SPOTLIGHT LIDER B MINI 830 23W 60° WHITE | ON/OFF

COB

80

3000 [K] |

3266 [lm]

2939 [lm]

128 [lm/W]

ON/OFF

3 SDCM

23 [W]

60°

Article number: N007-K0003-RF830-H5-M60-ZE53_600-S1-###



Spotli	ght	LED
--------	-----	-----

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

11	UI	ЛI	Ν	AI	R	E

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
Weight	0,85 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	WHITE			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

Plastic 220-240V 50-60Hz

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

Generated: 01.09.2024