

## SPOTLIGHT

## SPOTLIGHT LIDER B MINI 840 27W 15° WHITE | ON/OFF

Article number: N007-K0003-RF840-H5-M15-ZE53\_700-S1-###



Light colour	4000 [K]
CRI	80
Led chip flux	3974 [lm]
Luminous flux	3576 [lm]
System power	27 [W]
Luminaire Efficiency	132 [lm/W]
Beam angle	15°
Controller	ON/OFF
MacAdam	3 SDCM

COB

0,85 [kg]

WHITE

Plastic

IP 20, IK 1,

220-240V 50-60Hz

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska