

SPOTLIGHT

SPOTLIGHT LIDER B MINI 840 25W 60° WHITE | ON/OFF

COB

80

4000 [K] |

3690 [lm]

3321 [lm]

133 [lm/W]

ON/OFF

3 SDCM

25 [W]

60°

Article number: N007-K0003-RF840-H5-M60-ZE53_650-S1-###



Spotlight LED	Sp	otl	igh	it L	ED
---------------	----	-----	-----	------	----

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

- 11	JM	IN/	ΔIE	BE.

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
Weight	0,85 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	WHITE			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

Generated: 01.09.2024