

SPOTLIGHT

SPOTLIGHT LIDER B MINI 930 21W 38° WHITE | ON/OFF

Article number: N007-K0003-RF930-H5-M38-ZE53_550-S1-###



LED	COB	Spotlig
Light colour	3000 [K]	Compa installa colour a 60°. Ma
CRI	90	
Led chip flux	2536 [lm]	
Luminous flux	2282 [lm]	
System power	21 [W]	
Luminaire Efficiency	109 [lm/W]	
Beam angle	38°	
Controller	ON/OFF	
MacAdam	3 SDCM	

0,85 [kg]

WHITE

Plastic

IP 20, IK 1,

220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base nstallation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 50°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 01.09.2024