

SPOTLIGHT

SPOTLIGHT LIDER B MINI 940 14W 60° WHITE | ON/OFF

Article number: N007-K0003-RF940-H5-M60-ZE53_350-S1-###



MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	60°
Luminaire Efficiency	109 [lm/W]
System power	14 [W]
Luminous flux	1521 [lm]
Led chip flux	1691 [lm]
CRI	90
Light colour	4000 [K]

COB

0,85 [kg]

WHITE

Plastic

IP 20, IK 1,

220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 01.09.2024