

SPOTLIGHT LIDER B MINI 825 23W 15° WHITE BREAD ON/OFF

Article number: N007-K0003-VF825-H5-M15-ZE53_600-S1-###



| LED | COB | Spotlight LED |
|-----------------------------------|----------------|---|
| Light colour | 2500 [K] BREAD | Compact track mounted LED spot installation possible. Available in v colour available on enquiry. Refle 60°. Maximum power is 27W. |
| CRI | 80 | |
| Led chip flux | 2808 [lm] | |
| Luminous flux | 2527 [lm] | |
| System power | 23 [W] | |
| Luminaire Efficiency | 110 [lm/W] | |
| Beam angle | 15° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| UMINAIRE | | |
| Weight | 0,85 [kg] | |
| Protection rating IP , IK , class | IP 20, IK 1, | Note: All data are typical values |

WHITE

Plastic

220-240V 50-60Hz

otlight. Aluminium housing. Ceiling base n white, black and grey. Any RAL palette lector beams available: 15°, 23°, 38°, 45° and

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska