

SPOTLIGHT

SPOTLIGHT LIDER G 957 25W 45° GREY SPECIAL ON/OFF

Article number: N008-K0001-CC957-H5-M45-ZE51_650-S2-###



COB

90 3255 [lm]

2929 [lm]

25 [W] 117 [lm/W]

45°

ON/OFF

3 SDCM

5700 [K] SPECIAL



opolingin LED	S	ро	tli	gl	ht	LI	E	D
---------------	---	----	-----	----	----	----	---	---

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

may change with product improvements due to technical advances.

LUMINAIRE

Controller

MacAdam

Light colour

Led chip flux Luminous flux

System power

Luminaire Efficiency Beam angle

CRI

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

IP 20, IK 1, Note: All data are typical values. Tolerance of measurements +/-10% System features

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024