

SPOTLIGHT LIDER G 930 14W 15° GREY CRI97 ON/OFF

Article number: N008-K0001-HI930-H5-M15-ZE51_350-S2-###



COB

90

1575 [lm]

1417 [lm]

101 [lm/W]

ON/OFF

3 SDCM

14 [W]

15°

3000 [K] CRI97



Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Frotection rating IP, IK, class	IP 20, IK I,
uminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.