

SPOTLIGHT LIDER G 930 19W 45° GREY CRI97 ON/OFF

Article number: N008-K0001-HI930-H5-M45-ZE51_500-S2-###





COB

3000 [K] CRI97 Light colour

CRI

2199 [lm] Led chip flux Luminous flux 1979 [lm] System power 19 [W] Luminaire Efficiency 104 [lm/W] Beam angle 45° Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

0,69 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska