

## SPOTLIGHT LIDER G 930 10W 45° GREY CRI97 ON/OFF

Article number: N008-K0001-HI930-H5-M45-ZE61\_250-S2-###





COB

3000 [K] CRI97 Light colour

CRI

Led chip flux 1144 [lm] Luminous flux 1029 [lm] System power 10 [W] 103 [lm/W] Luminaire Efficiency Beam angle 45° Controller ON/OFF MacAdam 3 SDCM

## **Spotlight LED**

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

## LUMINAIRE

0,69 [kg] Weight Protection rating IP , IK , class IP 20, IK 1, GREY Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska