

SPOTLIGHT

SPOTLIGHT LIDER G 827 25W 15° GREY | ON/OFF

Article number: N008-K0001-RF827-H5-M15-ZE51_650-S2-###



COB

80 3502 [lm]

2700 [K] |

3151 [lm]

126 [lm/W]

ON/OFF

3 SDCM

25 [W]

15°



S	p	0	tli	ig	ht		Е	D
				-				

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

т	ш	٨	/11	N	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JIMINAIRE	
Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024