

SPOTLIGHT

SPOTLIGHT LIDER G 830 10W 45° GREY | ON/OFF

Article number: N008-K0001-RF830-H5-M45-ZE61_250-S2-###



COB

80

3000 [K] |

1361 [lm]

1224 [lm]

122 [lm/W]

ON/OFF

3 SDCM

10 [W]

45°



Spot	ight	LED
------	------	-----

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

т	ш	N	u	N	Δ	IR	F

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
Weight	0,69 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	GREY			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024