

SPOTLIGHT

SPOTLIGHT LIDER G 840 21W 45° GREY | ON/OFF

Article number: N008-K0001-RF840-H5-M45-ZE51_550-S2-###



СОВ

80 3122 [lm]

4000 [K] |

2809 [lm]

134 [lm/W]

ON/OFF

3 SDCM

21 [W]

45°



Sno	tlic	uht -	
Spu	ung	,	ᇆ

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

1.1	110	Л	N	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
Weight	0,69 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	GREY			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024