

SPOTLIGHT

SPOTLIGHT LIDER G 840 23W 45° GREY | ON/OFF

Article number: N008-K0001-RF840-H5-M45-ZE51_600-S2-###



СОВ

80 3407 [lm]

4000 [K] |

3066 [lm]

133 [lm/W]

ON/OFF

3 SDCM

23 [W]

45°



-				
<u> </u>	noti	lia	ht	
- 0	ρυι	пy	ш.	ᇆᄓ

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

т	ш	N	u	N	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE					
Weight	0,69 [kg]				
Protection rating IP , IK , class	IP 20, IK 1,				
Luminaire colour	GREY				
Cover	Plastic				
Operating voltage	220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024