

SPOTLIGHT

SPOTLIGHT LIDER G 850 23W 60° GREY | ON/OFF

Article number: N008-K0001-RF850-H5-M60-ZE51_600-S2-###



COB

80 3475 [lm]

5000 [K] |

3127 [lm]

136 [lm/W]

ON/OFF

3 SDCM

23 [W]

60°



| - | | | | |
|----------|------|-----|----|----|
| <u> </u> | noti | lia | ht | |
| - 0 | ρυι | пy | ш. | ᇆᄓ |

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

| т | ш | N | u | N | Δ | IR | F |
|---|---|---|---|---|---|----|---|

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| JANNAN IL | | | | | |
|-----------------------------------|------------------|--|--|--|--|
| Weight | 0,69 [kg] | | | | |
| Protection rating IP , IK , class | IP 20, IK 1, | | | | |
| Luminaire colour | GREY | | | | |
| Cover | Plastic | | | | |
| Operating voltage | 220-240V 50-60Hz | | | | |
| | | | | | |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.06.2024