

SPOTLIGHT

SPOTLIGHT LIDER G 940 14W 23° GREY | ON/OFF

Article number: N008-K0001-RF940-H5-M23-ZE51_350-S2-###



СОВ

90 1691 [lm]

4000 [K] |

1521 [lm]

109 [lm/W]

ON/OFF

3 SDCM

14 [W]

23°



-				
<u> </u>	noti	lia	ht	
- 0	ρυι	пy	ш.	ᇆᄓ

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

т	ш	N	u	N	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE					
Weight	0,69 [kg]				
Protection rating IP , IK , class	IP 20, IK 1,				
Luminaire colour	GREY				
Cover	Plastic				
Operating voltage	220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024