

## SPOTLIGHT

## SPOTLIGHT LIDER G 825 19W 15° GREY BREAD ON/OFF

Article number: N008-K0001-VF825-H5-M15-ZE51\_500-S2-###



COB

80 2340 [lm]

2106 [lm]

111 [lm/W]

ON/OFF

3 SDCM

19 [W]

15°

2500 [K] BREAD



-				
<u> </u>	noti	lia	ht	
- 0	ρυι	пy	ш.	ᇆᄓ

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

н	ш	M	IN	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
Weight	0,69 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	GREY			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska