

SPOTLIGHT LIDER G 935 14W 15° BLACK HI EFFICIENT ON/OFF

Article number: N008-K0002-BB935-H5-M15-ZE52_350-S2-###





LED COB

Light colour 3500 [K] HI EFFICIENT

CRI

2174 [Im] Luminous flux

System power 1956 [lm]

14 [W] Luminaire Efficiency

Beam angle

15°

ON/OFF

3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Controller

MacAdam

Led chip flux

Weight 0.69 [kg]

Protection rating IP , IK , class IP 20, IK 01,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-

60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

ic lecinical advanc

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

(€ EM 2K

Generated: 23.09.2024





