

SPOTLIGHT

SPOTLIGHT LIDER G 935 10W 60° BLACK HI EFFICIENT ON/OFF

Article number: N008-K0002-BB935-H5-M60-ZE62_250-S2-###





Light colour3500 [K] HI EFFICIENTCRI90Led chip flux1571 [Im]Luminous flux1413 [Im]System power10 [W]Luminaire Efficiency141 [Im/W]Beam angle60°ControllerON/OFFMacAdam3 SDCM	LED	COB
CRI90Led chip flux1571 [lm]Luminous flux1413 [lm]System power10 [W]Luminaire Efficiency141 [lm/W]Beam angle60°ControllerON/OFF	Light colour	
Led chip flux1571 [lm]Luminous flux1413 [lm]System power10 [W]Luminaire Efficiency141 [lm/W]Beam angle60°ControllerON/OFFMacAdamON/OFF	CRI	
Luminous flux1413 [lm]System power10 [W]Luminaire Efficiency141 [lm/W]Beam angle60°ControllerON/OFFMacAdamON/OFF	Led chip flux	90
System power1413 [lm]Luminaire Efficiency10 [W]Beam angle141 [lm/W]Controller60°MacAdamON/OFF	Lumineur flux	1571 [lm]
System power 10 [W] Luminaire Efficiency 141 [Im/W] Beam angle 60° Controller ON/OFF MacAdam ON/OFF	Luminous nux	1413 [lm]
Luminaire Efficiency 141 [Im/W] Beam angle 60° Controller ON/OFF MacAdam ON/OFF	System power	5 d
Beam angle 60° Controller 0N/OFF	Luminaire Efficiency	
60° Controller MacAdam	Poom angle	141 [lm/W]
ON/OFF		60°
MacAdam	Controller	
3 SDCM	MacAdam	ON/OFF
		3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024