

SPOTLIGHT LIDER G 930 23W 38° BLACK CRI97 ON/OFF

Article number: N008-K0002-HI930-H5-M38-ZE52_600-S2-###



3 SDCM



COB 3000 [K] CRI97 Light colour CRI Led chip flux 2601 [lm] Luminous flux 2340 [lm] System power 23 [W] Luminaire Efficiency 102 [lm/W] Beam angle 38° Controller ON/OFF

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

MacAdam

Weight 0,69 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 22.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska