

SPOTLIGHT

SPOTLIGHT LIDER G 930 14W 45° BLACK CRI97 ON/OFF

COB

90

1575 [lm]

1417 [lm]

101 [lm/W]

ON/OFF

3 SDCM

14 [W]

45°

3000 [K] CRI97

Article number: N008-K0002-HI930-H5-M45-ZE52_350-S2-###



c.	no	+li	al	ht.		
J	μυ	uı	ų	п.		
			۰.			

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

96 mm

LU	MI	NA	IRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,69 [kg]				
Protection rating IP , IK , class	IP 20, IK 1,				
Luminaire colour	BLACK				
Cover	Plastic				
Operating voltage	220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024