

### SPOTLIGHT

### SPOTLIGHT LIDER G 830 21W 60° BLACK | ON/OFF

Article number: N008-K0002-RF830-H5-M60-ZE52\_550-S2-###





UMINAIRE		
MacAdam	3 SDCM	_
Controller	ON/OFF	
Beam angle	60°	
Luminaire Efficiency	128 [lm/W]	
System power	21 [W]	
Luminous flux	2694 [lm]	
Led chip flux	2994 [lm]	
CRI	80	black and g available: 1
Light colour	3000 [K]	Compact tr

COB

#### Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, plack and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

## LUMINAIR

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024