

SPOTLIGHT

SPOTLIGHT LIDER G 840 10W 15° BLACK | ON/OFF

Article number: N008-K0002-RF840-H5-M15-ZE62_250-S2-###



СОВ

80 1419 [lm]

4000 [K] |

1277 [lm]

128 [lm/W]

ON/OFF

3 SDCM

10 [W]

15°



Spotlight LED	Spot		ht L	ED
---------------	------	--	------	----

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LU	MI	NA	IRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024