

SPOTLIGHT

SPOTLIGHT LIDER G 850 25W 60° BLACK | ON/OFF

Article number: N008-K0002-RF850-H5-M60-ZE52_650-S2-###



LED	COB	Spo
Light colour	5000 [K]	Con blac avai
CRI	80	
Led chip flux	3764 [lm]	
Luminous flux	3387 [lm]	
System power	25 [W]	
Luminaire Efficiency	135 [lm/W]	
Beam angle	60°	
Controller	ON/OFF	
MacAdam	3 SDCM	

0,69 [kg]

BLACK

Plastic

IP 20, IK 1,

220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, lack and grey. Any RAL palette colour available on enquiry. Reflector beams wailable: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

96 mm

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.06.2024