

SPOTLIGHT

SPOTLIGHT LIDER G 927 14W 15° BLACK | ON/OFF

Article number: N008-K0002-RF927-H5-M15-ZE52_350-S2-###





| LED | COB | Spotlight LED |
|-----------------------------------|--------------|---|
| Light colour | 2700 [K] | Compact track mounted LED spotlight. Aluminium hous black and grey. Any RAL palette colour available on en available: 15°, 23°, 38°, 45° and 60°. Maximum power i |
| CRI | 80 | |
| Led chip flux | 1555 [lm] | |
| Luminous flux | 1399 [lm] | |
| System power | 14 [W] | |
| Luminaire Efficiency | 100 [lm/W] | |
| Beam angle | 15° | |
| Controller | ON/OFF | |
| MacAdam | 3 SDCM | |
| LUMINAIRE | | |
| Weight | 0,69 [kg] | |
| Protection rating IP , IK , class | IP 20, IK 1, | Note: All data are typical values. Tolerance of measur |

BLACK

Plastic

220-240V 50-60Hz

otlight LED

ising. Available in white, nquiry. Reflector beams r is 25W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska