

SPOTLIGHT LIDER G 940 21W 15° BLACK | ON/OFF

Article number: N008-K0002-RF940-H5-M15-ZE52_550-S2-###



LED	COB
Light colour	4000 [K]
CRI	90
Led chip flux	2658 [lm]
Luminous flux	2392 [lm]
System power	21 [W]
Luminaire Efficiency	114 [lm/W]
Beam angle	15°
Controller	ON/OFF
MacAdam	3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Weight	0.69 [kg]
Protection rating IP , IK , class	IP 20, IK 01,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%
System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 24.09.2024



+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska