

## SPOTLIGHT

## SPOTLIGHT LIDER G 820 25W 23° BLACK MEAT PINK ON/OFF

Article number: N008-K0002-VE820-H5-M23-ZE52\_650-S2-###



IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic



black		LED	COB	Spotlig
CRI80availaLed chip flux2181 [lm]Luminous flux1962 [lm]System power25 [W]Luminaire Efficiency78 [lm/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM		Light colour	2000 [K] MEAT PINK	Compa
Luminous flux1962 [lm]System power25 [W]Luminaire Efficiency78 [lm/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM		CRI	80	black aı availabl
System power25 [W]Luminaire Efficiency78 [Im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM		Led chip flux	2181 [lm]	
Luminaire Efficiency 78 [Im/W]   Beam angle 23°   Controller ON/OFF   MacAdam 3 SDCM		Luminous flux	1962 [lm]	
Beam angle 23° Controller ON/OFF MacAdam 3 SDCM		System power	25 [W]	
Controller ON/OFF MacAdam 3 SDCM		Luminaire Efficiency	78 [lm/W]	
MacAdam 3 SDCM		Beam angle	23°	
LUMINAIRE		Controller	ON/OFF	
		MacAdam	3 SDCM	
Weight 0,69 [kg]	ļ	LUMINAIRE		
		Weight	0,69 [kg]	

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, lack and grey. Any RAL palette colour available on enquiry. Reflector beams vailable: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

 $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024