

SPOTLIGHT

SPOTLIGHT LIDER G 930 21W 15° WHITE HI EFFICIENT ON/OFF

Article number: N008-K0003-BB930-H5-M15-ZE53_550-S2-###





Light colour3000 [K] HI EFFICIENTCRI90Led chip flux3487 [Im]Luminous flux3138 [Im]System power21 [W]Luminaire Efficiency149 [Im/W]Beam angle15°ControllerON/OFFMacAdam3 SDCM	LED	COB
Led chip flux90Luminous flux3487 [lm]System power3138 [lm]Luminaire Efficiency21 [W]Beam angle149 [lm/W]Controller15°MacAdamON/OFF	Light colour	
Led chip flux3487 [lm]Luminous flux3138 [lm]System power21 [W]Luminaire Efficiency149 [lm/W]Beam angle15°ControllerON/OFFMacAdamController	CRI	00
Luminous flux3138 [lm]System power21 [W]Luminaire Efficiency149 [lm/W]Beam angle15°ControllerON/OFFMacAdamController	Led chip flux	
System power3138 [lm]Luminaire Efficiency21 [W]Beam angle149 [lm/W]Controller15°MacAdamON/OFF	Luminous flux	3487 [lm]
21 [W] Luminaire Efficiency 149 [Im/W] Beam angle 15° Controller ON/OFF		3138 [lm]
149 [lm/W] Beam angle Controller MacAdam		21 [W]
Beam angle 15° Controller ON/OFF		149 [lm/W]
Controller ON/OFF MacAdam	Beam angle	L d
MacAdam	Controller	15°
	MacAdam	ON/OFF
	MacAdam	3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl 0

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024