

## SPOTLIGHT LIDER G 930 25W 15° WHITE HI EFFICIENT ON/OFF

Article number: N008-K0003-BB930-H5-M15-ZE53\_650-S2-###





LED COB

Light colour 3000 [K] HI EFFICIENT

CRI

Led chip flux 4084 [lm]

Luminous flux 3675 [lm]

System power 25 [W]

Luminaire Efficiency 147 [lm/W]

Beam angle 15°

Controller ON/OFF

MacAdam 3 SDCM

## **Spotlight LED**

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

## **LUMINAIRE**

Weight 0.69 [kg] Protection rating IP, IK, class IP 20, IK 01,

Luminaire colour WHITE

Plastic Cover

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to

technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

CE EN EK





