

SPOTLIGHT

SPOTLIGHT LIDER G 930 21W 45° WHITE HI EFFICIENT ON/OFF

Article number: N008-K0003-BB930-H5-M45-ZE53_550-S2-###





LED	СОВ
Light colour	3000 [K] HI EFFICIENT
CRI	
Led chip flux	90
Luminous flux	3487 [lm]
Luminous nux	3138 [lm]
System power	21 [W]
Luminaire Efficiency	
Beam angle	149 [lm/W]
	45°
Controller	ON/OFF
MacAdam	UN/OFF
	3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska