

SPOTLIGHT LIDER G 930 23W 60° WHITE HI EFFICIENT ON/OFF

Article number: N008-K0003-BB930-H5-M60-ZE53_600-S2-###





COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 3787 [lm] Luminous flux 3408 [lm] System power 23 [W] Luminaire Efficiency 148 [lm/W] Beam angle 60° Controller ON/OFF MacAdam 3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Weight 0,69 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 23.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska