

## SPOTLIGHT LIDER G 930 14W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N008-K0003-HE930-HA-M45-ZE53\_350-S2-###





\_ED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 2064 [lm]

 Luminous flux
 1857 [lm]

 System power
 14 [W]

 Luminaire Efficiency
 133 [lm/W]

 Beam angle
 45°

 Controller
 45°

Controller

MacAdam

3 SDCM

## LUMINAIRE

Weight 0,69 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 23.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska