

## SPOTLIGHT LIDER G 930 21W 23° WHITE CRI97 ON/OFF

Article number: N008-K0003-HI930-H5-M23-ZE53\_550-S2-###



COB

90 2402 [lm]

2161 [lm]

103 [lm/W]

ON/OFF

3 SDCM

21 [W]

23°

3000 [K] CRI97



Sno	tlic	uht -	
Spu	ung	,	ᇆ

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

н	ш	M	IN	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,69 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	WHITE			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

## may change with product improvements due to technical advances.

## OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 21.06.2024